

www.rhinotufftanks.com customerservice@rhinotufftanks.com

(877) 788-8332

Fax (320) 963-6192

Effectively organize your bulk fluid inventory, eliminate the hassle of handling 55-gallon drums, and maximize valuable floor space with Rhino Tuff Tanks stackable tank systems. Individual tanks are designed with a common 36" x 36" footprint among all sizes. Tanks can be securely stacked with each other in any combination without requiring costly conversion brackets or racking. Using Natural Virgin High-Density Polyethylene resins, Rhino Ruff Tanks provide a clean, stable, contamination-free container that will not rust or corrode – protecting your fluids from the environment. Combine with any array of accessories to create your own unique storage and dispensing system. RTT systems have been certified as compliant with ULC 142.14-03 and UL-2152 testing standards and bear the markings as such.

Description:

225 GALLON GRAVITY FEED TANK PACKAGE

Model: RTT-6400-NV

P/N: 500393

Package Includes:

- One (1) 225 Gallon Stackable Tank
- Tank stand with 24" legs
- Drip Tray Kit
- Accessory Package that includes:
 - Braided Poly Tubing
 - Stainless Steel Elbow Adapter with Barbed End
 - 1" Hose Clamps
 - Thread Sealant Tape
 - Stainless Steel Elbow Kit with Nut for Stand

Valves will be needed based upon your fluid application. Refer to the chemical compatibility chart for more information.







Stackable Tank Features:

- (2) 2" NPT top openings for pump or vent application **Dispensing Valves Sold Separately**
- 1" opening for desiccant breather or remote fill **Shown with RTT-4001 Brass Spring Release Valve**
- Convenient 2" center fill opening
- Interlocking top and bottom ridges for secure stacking
- Six molded-in 5/16-18 metal inserts allow for side mount pump plate to be attached
- Serialized graphic and identification label
- (2) 1" NPT Molded-in 304 Stainless Steel Bushing at drain openings
- Molded-in site gauge and semi-transparent material eliminates the need for external site gauges
- Natural virgin high-density polyethylene construction
- Stackable in any combination no converting brackets needed
- See your exact fluid levels
- Standard 3' x 3' footprint among all sizes

Specifications:

SHIPPING DIMS	SHIPPING WEIGHT	ASSEMBLED	TANK	SYSTEM CAPACITY (US GAL / L)
(INCL PALLET)	(INCL PALLET)	DIMENSIONS	QTY	
44" L X 36" W X 60" H	275LBS	36" L X 42" W X 78" H	1	225 US GAL / 852 L









